

Polystyrene

General Purpose

PROCESS FLOW DIAGRAM

Page 1 of 1

Polystyrene - General Purpose

Valve Number	Valve Description	Design Temperature Range		Design Pressure Range		Pipe Size		Recommended Valve ¹						
		deg F	deg C	psig	bar g	in	dn	C-Series	T-Series	G-Series	ISOLATOR 2.0	IRSVP	Watson Series	FlexStream®
1	Fresh Styrene	150	66	150	10	2 – 4	50 – 100				•			
2	Fresh Solvent	150	66	150	10	2 – 4	50 – 100				•			
3	Recycle Solvent	250 – 350	121 – 177	150	10	2 – 4	50 – 100				•			
4	Main Pump	250 – 350	121 – 177	150	10	2 – 8	50 – 200				•			
5	Reactor	250 – 350	121 – 177	150	10	2 – 8	50 – 200				•			
6	Devolatilizer	250 – 350	121 – 177	150	10	2 – 8	50 – 200							
	Heat Exchanger	300 – 1000	149 – 538	200 – 600	14 – 41	1/2 – 2	15 – 50					•		
	General Ball Valves	600 – 700	316 – 371	100 – 600	7 – 41	1 – 3	25 – 75			•				

¹ Recommend ISOLATOR 2.0 or T-Series if size, pressure and temperature conditions are met.

